



```

LL          IIIIII  SSSSSSSS
LL          IIIIII  SSSSSSSS
LL          II      SS
LL          II      SS
LL          II      SS
LL          II      SS
LL          II      SSSSSS
LL          II      SSSSSS
LL          II      SS
LL          II      SS
LL          II      SS
LL          II      SS
LLLLLLLLLLLL IIIIII  SSSSSSSS
LLLLLLLLLLLL IIIIII  SSSSSSSS

```

MTHSCGSQRT  
Table of contents

K 5

16-SEP-1984 01:10:12 VAX/VMS Macro V04-00

Page 0

(2)	49	HISTORY	; Detailed Current Edit History
(3)	57	DECLARATIONS	
(4)	84	MTHSCGSQRT	- compute G COMPLEX*16 square root

MTH  
Sym

ARG  
MTH  
MTH  
MTH  
MTH  
MTH

PSE  
---

MT

Pha  
---  
Ini  
Com  
Pas  
Sym  
Pas  
Sym  
Pse  
Cro  
Ass

The  
213  
The  
197  
1 p

Mac  
---  
\_ \$2

0 G

The

MAC

```
0000 1      .TITLE MTH$CGSQRT
0000 2      .IDENT /1-002/      ; File: MTHCSQRT.MAR SBL1002
0000 3
0000 4
0000 5      *****
0000 6      *
0000 7      *  COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0000 8      *  DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0000 9      *  ALL RIGHTS RESERVED.
0000 10     *
0000 11     *  THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0000 12     *  ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0000 13     *  INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0000 14     *  COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0000 15     *  OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0000 16     *  TRANSFERRED.
0000 17     *
0000 18     *  THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0000 19     *  AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0000 20     *  CORPORATION.
0000 21     *
0000 22     *  DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0000 23     *  SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0000 24     *
0000 25     *
0000 26     *****
0000 27
0000 28
0000 29     FACILITY: MATH LIBRARY
0000 30     ++
0000 31     ABSTRACT:
0000 32         This module contains routine MTH$CGSQRT - compute
0000 33         G COMPLEX*16 square root.
0000 34
0000 35     --
0000 36
0000 37     VERSION: 1
0000 38
0000 39     HISTORY:
0000 40
0000 41     AUTHOR:
0000 42         Steven B. Lionel, 24-July-1979
0000 43
0000 44     MODIFIED BY:
0000 45
0000 46
0000 47
```



MTH\$CGSQRT  
1-002

M 5

HISTORY ; Detailed Current Edit History 16-SEP-1984 01:10:12 VAX/VMS Macro V04-00 Page 2  
6-SEP-1984 11:21:11 [MTHRTL.SRC]MTH\$CGSQRT.MAR;1 (2)

0000 49 .SBTTL HISTORY ; Detailed Current Edit History  
0000 50  
0000 51  
0000 52 ; Edit History  
0000 53  
0000 54 ; 1-001 - Adapted from MTH\$CSQRT version 1-003. SBL 24-July-1979  
0000 55 ; 1-002 - Use general mode addressing. SBL 30-Nov-1981

MTH  
Tab

## DECLARATIONS

```
0000 57      .SBTTL DECLARATIONS
0000 58
0000 59 :
0000 60 : INCLUDE FILES:
0000 61 :
0000 62 :
0000 63 :
0000 64 : EXTERNAL SYMBOLS:
0000 65      .DSABL  GBL
0000 66      .EXTRN  MTH$CGABS
0000 67      .EXTRN  MTH$GSQRT_RS
0000 68
0000 69 :
0000 70 : MACROS:
0000 71 :     NONE
0000 72 :
0000 73 :
0000 74 : PSECT DECLARATIONS:
0000 75      .PSECT  _MTH$CODE      PIC, SHR, LONG, EXE, NOWRT
0000 76
0000 77 :
0000 78 : EQUATED SYMBOLS:
0000 79 :
0000 80 :
0000 81 : OWN STORAGE:
0000 82 :     NONE
```

MTH\$CGSQRT - compute G COMPLEX\*16 square

```
0000 84      .SBTTL MTH$CGSQRT - compute G COMPLEX*16 square root
0000 85
0000 86      :++
0000 87      : FUNCTIONAL DESCRIPTION:
0000 88      :
0000 89      : The square root of a complex number (r, i) is computed
0000 90      : as follows:
0000 91
0000 92      : ROOT = SQRT((ABS(r) + CABS((r, i))) / 2)
0000 93      : Q = i / (2*ROOT)
0000 94
0000 95
0000 96      : r      i      CSQRT((r, i))
0000 97      : -      -      -----
0000 98
0000 99      : >=0    any    (ROOT, Q)
0000 100     : <0     >=0    (Q, ROOT)
0000 101     : <0     <0    (-Q, -ROOT)
0000 102
0000 103     : CALLING SEQUENCE:
0000 104
0000 105     : CALL MTH$CGSQRT (result.wgc.r, arg.rgc.r)
0000 106
0000 107     : INPUT PARAMETERS:
0000 108
00000008 0000 109     : arg      = 8          ; The G COMPLEX*16 argument, passed
0000 110     :                               ; by reference.
0000 111
0000 112     : IMPLICIT INPUTS:
0000 113     : NONE
0000 114
0000 115     : OUTPUT PARAMETERS:
00000004 0000 116
0000 117     : result = 4          ; The G COMPLEX*16 result, passed by
0000 118     :                               ; reference.
0000 119
0000 120     : IMPLICIT OUTPUTS:
0000 121     : NONE
0000 122
0000 123     : COMPLETION CODES:
0000 124     : NONE
0000 125
0000 126     : SIDE EFFECTS:
0000 127
0000 128     : SS$_ROPRAND      If either part of argument is reserved operand.
0000 129
0000 130     : --
0000 131
0000 132
007C 0000 133     : .ENTRY MTH$CGSQRT,      ^M<R2, R3, R4, R5, R6>
0002 134     : MTH$FLAG_JACKET      ; flag as math routine
0002
6D 00000000'GF 9E 0002     : MOVAB G^MTH$$JACKET_HND, (FP)
0009     :                               ; set handler address to jacket
0009     :                               ; handler
0009
0009 135
```

```

52 08 BC 50FD 0009 136      MOVG      @arg(AP), R2      ; R2-R3 = r
52 8000 8F AA 000E 137      BICW      #^X8000, R2      ; R2-R3 = ABS(r)
08 AC DD 0013 138      PUSHL     arg(AP)      ; Put address of arg on stack
00000000'GF 01 FB 0016 139      CALLS     #1, G^MTH$CGABS      ; R0-R1 = CABS((r, i))
50 52 40FD 001D 140      ADDG2     R2, R0      ; R0-R1 = ABS(r) + CABS((r, i))
50 00 44FD 0021 141      MULG2     #0.5, R0      ; R0-R1 = (ABS(r) + CABS((r, i))) / 2
00000000'GF 16 0025 142      JSB      G^MTH$GSQRT_R5      ; R0-R1 = ROOT = SQRT(above)
52 08 AC 50 002B 143      MOVL      arg(AP), R2      ; R2 -> (r, i)
50 53FD 002F 144      TSTG      R0      ; is ROOT zero?
04 12 0032 145      BNEQ      1$      ; no, go ahead
55 7C 0034 146      CLRG      R5      ; make zero quotient
0A 11 0036 147      BRB      2$      ; skip divide
55 08 A2 50 47FD 0038 148 1$: DIVG3     R0, 8(R2), R5      ; R5 = i / ROOT
55 00 44FD 003E 149      MULG2     #0.5, R5      ; R5 = Q = i / (2 * ROOT)
82 53FD 0042 150 2$: TSTG      (R2)+      ; if r positive
18 18 0045 151      BGEQ      RETRN      ; then return (ROOT, Q)
53 50 7D 0047 152      MOVQ      R0, R3      ; else switch ROOT and Q
62 53FD 004A 153      TSTG      (R2)      ; if i positive
0A 18 004D 154      BGEQ      RETRN1     ; then return (Q, ROOT)
50 55 52FD 004F 155      MNEGG     R5, R0      ; else negate ROOT and Q
55 53 52FD 0053 156      MNEGG     R3, R5      ; and return (-Q, -ROOT)
06 11 0057 157      BRB      RETRN
0059 158
0059 159 RETRN1: MOVQ      R5, R0      ; continue to swap ROOT and Q
50 55 7D 0059 160      MOVQ      R3, R5      ; and return (Q, ROOT)
55 53 7D 005C 161
005F 162 RETRN: MOVL      result(AP), R2      ; result address
52 04 AC D0 005F 163      MOVQ      R0, (R2)+      ; real part
82 50 7D 0063 164      MOVQ      R5, (R2)      ; imaginary part
62 55 7D 0066 165
04 0069 166      RET
006A 167
006A 168
006A 169      .END
```



MTHSCGSQRT  
Symbol table

D 6

16-SEP-1984 01:10:12 VAX/VMS Macro V04-00  
6-SEP-1984 11:21:11 [MTHRTL.SRC]MTHCGSQRT.MAR;1

Page 6  
(4)

ARG = 00000008  
MTH\$\$JACKET\_HND \*\*\*\*\* X 01  
MTH\$CGABS \*\*\*\*\* X 00  
MTH\$CGSQRT 00000000 RG 01  
MTH\$GSQRT\_R5 \*\*\*\*\* X 00  
RCSULT = 00000004  
RETRN 0000005F R 01  
RETRN1 00000059 R 01

-----  
! Psect synopsis !  
-----

PSECT name	Allocation	PSECT No.	Attributes														
ABS	00000000 ( 0.)	00 ( 0.)	NOPIC	USR	CON	ABS	LCL	NOSHR	NOEXE	NORD	NOWRT	NOVEC	BYTE				
MTH\$CODE	0000006A ( 106.)	01 ( 1.)	PIC	USR	CON	REL	LCL	SHR	EXE	RD	NOWRT	NOVEC	LONG				

-----  
! Performance indicators !  
-----

Phase	Page faults	CPU Time	Elapsed Time
Initialization	37	00:00:00.08	00:00:00.58
Command processing	122	00:00:00.64	00:00:04.27
Pass 1	89	00:00:00.72	00:00:02.57
Symbol table sort	0	00:00:00.00	00:00:00.00
Pass 2	45	00:00:00.50	00:00:02.14
Symbol table output	2	00:00:00.02	00:00:00.23
Psect synopsis output	2	00:00:00.02	00:00:00.02
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	299	00:00:01.98	00:00:09.81

The working set limit was 900 pages.  
2877 bytes (6 pages) of virtual memory were used to buffer the intermediate code.  
There were 10 pages of symbol table space allocated to hold 8 non-local and 2 local symbols.  
229 source lines were read in Pass 1, producing 11 object records in Pass 2.  
1 page of virtual memory was used to define 1 macro.

-----  
! Macro library statistics !  
-----

Macro library name	Macros defined
_\$255\$DUA28:[SYSLIB]STARLET.MLB;2	0

0 GETS were required to define 0 macros.

There were no errors, warnings or information messages.

MACRO/ENABLE=SUPPRESSION/DISABLE=(GLOBAL,TRACEBACK)/LIS=LIS\$:MTHCGSQRT/OBJ=OBJ\$:MTHCGSQRT MSRC\$:MTHJACKET/UPDATE=(ENH\$:MTHJACKET)+MS



0258 AH-BT13A-SE  
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION  
CONFIDENTIAL AND PROPRIETARY